

## Product / Type / Code

# PREFASEC® LIGHT

The product codes are which appear in the Technical File of the product PREFASEC® LIGHT.

## The Manufacturer

MORTEROS TUDELA VEGUÍN, S.A. - C/ Argüelles, 25. 33003 Oviedo, Asturias. España.

System of assessment and verification of constancy of performance: 2+.

## Notified body

AENOR (Asociación Española de Normalización y Certificación) - 0099

Performed: Certification of conformity of the factory production control

Under system: 2+

Document issued: 0099/CPR/A69/0454

Date: 23.01.2013

## Intended uses and Declared Performance

### LIGHT MASONRY MORTAR (L) EN 998-2:2010

Intended uses: - Indoor and outdoor - Reinforced brickwork - With structural demands  
- Constructions subjected to requirements regarding fire. - With thermal insulation demands

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1	
Chloride content	< 0.1 %	
Steam permeability	$\mu$ 5/20	
Thermal conductivity ( $\lambda_{10, dry}$ )	$\leq 0.39$ W/m·K	EN 998-2:2010
Initial shearing resistance	0.15 N/mm <sup>2</sup>	
Compression strength (N/mm <sup>2</sup> )	<b>M7.5</b> $\geq 7.5$	
Water absorption	<b>NORMAL</b> $\leq 1.50$ kg/m <sup>2</sup> ·min <sup>0.5</sup>	<b>WATER-REPELLENT</b> $\leq 0.20$ kg/m <sup>2</sup> ·min <sup>0.5</sup>

*The performance of the product identified on top is in conformity with the declared performance in table.*

*This declaration of performance is issued under the sole responsibility of the manufacturer identified in this document.*

*For information about safety and hygiene check the Safety Data Sheet of the product.*



Juan José Iglesias Huelga  
Gerente Morteros