

Declaration of Performance



Product / Type / Code

PREFASEC[®] RENDER

The product codes are which appear in the Technical File of the product PREFASEC® RENDER.

The Manufacturer

MORTEROS TUDELA VEGUÍN, S.A. - C/ Argüelles, 25. 33003 Oviedo, Asturias. España.

System of assessment and verification of constancy of performance: 4.

Intended uses and Declared Performance

RENDERING MORTAR (GP) COLOURED RENDERING M Intended uses: - For walls	ORTAR (CR) EN 998-1:201		water-repellent)
Essential charecteristics		Performance	Harmonised technical specification
Reaction to fire		A1	
Steam permeability		μ 5/20	
Thermal conductivity ($\lambda_{10, dry}$)		≤ 0.67 W/m·K	EN 998-1:2010
Adhesion strength		≥ 0.3 N/mm ² – FP: B	
Water absorption	NORMAL W0: Not specified	WATER-REPELLEN W2: ≤ 0.20 kg/m²⋅mi	

The performace of the product identified on top is in conformity with the declared performance in table.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in this document.

For information about safety and hygiene check the Safety Data Sheet of the product.

Juan José Iglesias Huelga Gerente Morteros

MASAVEU . INDUSTRIA