

Product / Type / Code

AGGREGATE CONCRETE MASONRY UNITS

The product codes are which appear in the next page.

The Manufacturer

MORTEROS TUDELA VEGUÍN, S.A. - C/ Argüelles, 25. 33003 Oviedo, Asturias. España.

System of assessment and verification of constancy of performance: 4.

Intended uses and Declared Performance

AGGREGATE CONCRETE MASONRY UNITS (DENSE AGGREGATES – Cat. II) EN 771-3:2011

Intended uses:	- Indoor and outdoor	- Reinforced brickwork	- With structural demands
	- Constructions subjected to requirements regarding fire.		- With thermal insulation demands
Essential characteristics	Performance		Harmonised technical specification
	Clase A1		
Steam permeability	μ 5/15		
Average normalized compression strength (N/mm ²)	≥ 8		
Absolute density (kg/m ³)	2100 ± 100		EN 771-3:2011
Dimensional tolerances (mm)	± 3		
Water absorption	NORMAL NPD	WATER-REPELLENT < 3 g/m².s	

Configuration: view next page









Las prestaciones del producto identificado son conformes con las indicadas en la tabla.

La presente declaración de prestaciones se emite bajo la única responsabilidad del fabricante indicado en este documento.

Ver la Ficha de Datos de Seguridad del producto para consultar los posibles riesgos particulares del mismo.



Juan José Iglesias Huelga
Gerente Morteros

FLAT BLOCK		GROOVED FLAT BLOCK		SPLIT BLOCK	
					
A = 29 - 19 - 14 - 12 - 9		A = 19 - 14 - 12 - 9		A = 19 - 14	
Normal	Water-repellent	Normal	Water-repellent	Normal	Water-repellent
L-290 L-190 L-140 L-120 L-90	L-290-H/B/C/S L-190-H/B/C/S L-140-H/B/C/S L-120-H/B/C/S L-90-H/B/C/S	LR-190 LR-140 LR-120 LR-90	LR-290-H/B/C/S LR-190-H/B/C/S LR-140-H/B/C/S LR-120-H/B/C/S LR-90-H/B/C/S	S-190 S-140	S-190-H/B/C/S S-140-H/B/C/S DS-190-H/B/C/S
HALF-HEIGHT SPLIT BLOCK		DOUBLE FACE SPLIT BLOCK		RUDOLPH BLOCK	
					
A = 19 - 14		A = 19		A = 19 - 14	
Normal	Water-repellent	Normal	Water-repellent	Normal	Water-repellent
	SM-190-H/B/C/S SM-140-H/B/C/S		DS-190-H/B/C/S	R-190 R-140	R-190-H/B/C/S R-140-H/B/C/S
DIAMOND POINT BLOCK		HACKLED BLOCK			
					
A = 19 - 14		A = 19 - 14 - 12 - 9			
Normal	Water-repellent	Normal	Water-repellent		
	D-190-H/B/C/S D-140-H/B/C/S	P-190 P-140 P-120 P-90	P-190-H/B/C/S P-140-H/B/C/S P-120-H/B/C/S P-90-H/B/C/S		