

Declaration of Performance



Product / Type / Code

CEMENCOL[®] C2 PORCELANIC

The product codes are which appear in the Technical File of the product CEMENCOL® C2 PORCELANIC.

The Manufacturer

MORTEROS TUDELA VEGUÍN, S.A. - C/ Argüelles, 25. 33003 Oviedo, Asturias. España.

System of assessment and verification of constancy of performance: 3.

Notified body

LGAI Technological Center, S.A. - 0370

Performed: Type testing

Under system: 3

Document issued: 5022078

Date: 31.05.2005

Intended uses and Declared Performance

CEMENT ADHESIVE EN 12004:2007+A1:2012

Intended uses: - Horizontal and vertical surfaces - Indoor and outdoor

Essential charecteristics	Performance	Harmonised technical specification
Initial bond strength (28 días)	\geq 1.0 N/mm ²	EN 12004:2007+A1:2012
Bond strength after immersion in water	\geq 1.0 N/mm ²	
Bond strength alter application of heat source	\geq 1.0 N/mm ²	
Bond strength alter after freeze-thaw cycles	\geq 1.0 N/mm ²	
Reaction to fire	A1 / A1 _{fi}	

The performace of the product identified on top is in conformity with the declared performance in table.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in this document.

For information about safety and hygiene check the Safety Data Sheet of the product.

Juan José Iglesias Huelga Gerente Morteros

Oviedo - Rev.00 - Date: 01.07.2013

MASAVEU . INDUSTRIA