

Product / Type / Code

PREFASEC® THERM. ETICS MORTAR

The product codes are which appear in the Technical File of the product PREFASEC® THERM ETICS MORTAR.

The Manufacturer

MORTEROS TUDELA VEGUÍN, S.A. - C/ Argüelles, 25. 33003 Oviedo, Asturias. España.

System of assessment and verification of constancy of performance: 4.

Intended uses and Declared Performance

RENDERING MORTAR (GP) EN 998-1:2016

Intended uses: - For walls, ceilings, pillars and partitions - Indoor and outdoor

Essential characteristics	Performance	Harmonised technical specification
Adhesion strength	$\geq 0.5 \text{ N/mm}^2$ – FP: B	EN 998-1:2016
Steam permeability	μ 5/20	
Thermal conductivity ($\lambda_{10, \text{dry}}$)	$\leq 0.67 \text{ W/m}\cdot\text{K}$	
Water absorption	W2: $\leq 0.20 \text{ kg/m}^2\cdot\text{min}^{0.5}$	
Reaction to fire	Class F	
Release of dangerous substances	Check the Safety Data Sheet	

The performance of the product identified on top is in conformity with the declared performance in table.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in this document.

For information about safety and hygiene check the Safety Data Sheet of the product.



Juan José Iglesias Huelga
Gerente Morteros